

Model	Version	Shock Size	Fork Travel	Rear Travel	Wheel size
Tallboy/Joplin 4		190x45	130	120	29

D Kit

Shock

Fox Float Performance

Rider Weight (lbs)	(kgs)	Pressure (psi)	Sag (% mm on shock)	Rebound (from closed)	Rebound (Jul, from closed)
100	45	110	29-32%, 13-14.5mm	9	8
120	54	135	29-32%, 13-14.5mm	9	8
140	64	160	29-32%, 13-14.5mm	8	7
160	73	185	29-32%, 13-14.5mm	8	7
180	82	210	29-32%, 13-14.5mm	7	6
200	91	235	29-32%, 13-14.5mm	7	5
220	100	260	29-32%, 13-14.5mm	6	4
240	109	285	29-32%, 13-14.5mm	6	4
260	118	310	29-32%, 13-14.5mm	5	3

Fork

Rockshox Rekon Silver RL 130

Rider Weight (lbs)	(kgs)	Pressure (psi)	Rebound (from closed)
100	45	50	5
120	54	60	5
140	64	70	5
160	73	85	4
180	82	100	3
200	91	120	3
220	100	140	2
240	109	155	1

Tallboy/Joplin

R Kit

Shock

Fox Float Performance

Rider Weight (lbs)	(kgs)	Pressure (psi)	Sag (% mm on shock)	Rebound (from closed)	Rebound (Jul, from closed)
100	45	110	29-32%, 13-14.5mm	9	8
120	54	135	29-32%, 13-14.5mm	9	8
140	64	160	29-32%, 13-14.5mm	8	7
160	73	185	29-32%, 13-14.5mm	8	7
180	82	210	29-32%, 13-14.5mm	7	6
200	91	235	29-32%, 13-14.5mm	7	5
220	100	260	29-32%, 13-14.5mm	6	4
240	109	285	29-32%, 13-14.5mm	6	4
260	118	310	29-32%, 13-14.5mm	5	3

Fork

Fox Rhythm 34 130

Rider Weight (lbs)	(kgs)	Pressure (psi)	Rebound (from closed)
120-130	54-59	58	13
130-140	59-64	63	12
140-150	64-68	68	11
150-160	68-73	72	10
160-170	73-77	77	9
170-180	77-82	82	8
180-190	82-86	86	7
190-200	86-91	91	6
200-210	91-95	96	5
210-220	95-100	100	4
220-230	100-104	105	3
230-240	104-109	110	2
240-250	109-113	114	1

Tallboy/Joplin

S Kit

Shock

Fox Float Performance

Rider Weight (lbs)	(kgs)	Pressure (psi)	Sag (% mm on shock)	Rebound (from closed)	Rebound (Jul, from closed)
100	45	110	29-32%, 13-14.5mm	9	8
120	54	135	29-32%, 13-14.5mm	9	8
140	64	160	29-32%, 13-14.5mm	8	7
160	73	185	29-32%, 13-14.5mm	8	7
180	82	210	29-32%, 13-14.5mm	7	6
200	91	235	29-32%, 13-14.5mm	7	5
220	100	260	29-32%, 13-14.5mm	6	4
240	109	285	29-32%, 13-14.5mm	6	4
260	118	310	29-32%, 13-14.5mm	5	3

Fork

Fox Performance 34 130

Rider Weight (lbs)	(kgs)	Pressure (psi)	Rebound (from closed)
120-130	54-59	58	13
130-140	59-64	63	12
140-150	64-68	68	11
150-160	68-73	72	10
160-170	73-77	77	9
170-180	77-82	82	8
180-190	82-86	86	7
190-200	86-91	91	6
200-210	91-95	96	5
210-220	95-100	100	4
220-230	100-104	105	3
230-240	104-109	110	2
240-250	109-113	114	1

Tallboy/Joplin

XT Kit**Shock**

Fox Float Perf. Elite

Rider Weight (lbs)	(kgs)	Pressure (psi)	Sag (% mm on shock)	Rebound (from closed)	Rebound (Juli, from closed)
100	45	110	29-32%, 13-14.5mm	9	8
120	54	135	29-32%, 13-14.5mm	9	8
140	64	160	29-32%, 13-14.5mm	8	7
160	73	185	29-32%, 13-14.5mm	8	7
180	82	210	29-32%, 13-14.5mm	7	6
200	91	235	29-32%, 13-14.5mm	7	5
220	100	260	29-32%, 13-14.5mm	6	4
240	109	285	29-32%, 13-14.5mm	6	4
260	118	310	29-32%, 13-14.5mm	5	3

Fork

Fox Perf. Elite 34 G2 130

Rider Weight (lbs)	(kgs)	Pressure (psi)	Rebound: LSR,HSR (from closed)	Compression: LSC,HSC (from closed)
120-130	54-59	58	9, 8	10,5
130-140	59-64	63	8, 7	10,5
140-150	64-68	68	7, 6	10,5
150-160	68-73	72	7, 6	10,5
160-170	73-77	77	6, 5	10,5
170-180	77-82	82	6, 5	10,5
180-190	82-86	86	5, 4	10,5
190-200	86-91	91	4, 3	10,5
200-210	91-95	96	4, 3	10,5
210-220	95-100	100	3, 2	10,5
220-230	100-104	105	2, 1	10,5
230-240	104-109	110	2, 1	10,5
240-250	109-113	114	1, 0	10,5

Tallboy/Joplin

XX1 Kit**Shock**

Fox Float Factory

Rider Weight (lbs)	(kgs)	Pressure (psi)	Sag (% mm on shock)	Rebound (from closed)	Rebound (Juli, from closed)
100	45	110	29-32%, 13-14.5mm	9	8
120	54	135	29-32%, 13-14.5mm	9	8
140	64	160	29-32%, 13-14.5mm	8	7
160	73	185	29-32%, 13-14.5mm	8	7
180	82	210	29-32%, 13-14.5mm	7	6
200	91	235	29-32%, 13-14.5mm	7	5
220	100	260	29-32%, 13-14.5mm	6	4
240	109	285	29-32%, 13-14.5mm	6	4
260	118	310	29-32%, 13-14.5mm	5	3

Fork

Rockshox Pike Ultimate 130

Rider Weight (lbs)	(kgs)	Pressure (psi)	Rebound (from closed)	Compression: LSC,HSC (from closed)
100	45	50	12	9,4
120	54	60	11	9,4
140	64	70	10	9,4
160	73	80	10	9,4
180	82	90	9	9,4
200	91	100	7	9,4
220	100	110	6	9,4
240	109	120	5	9,4

Tallboy/Joplin

XX1 Kit**Shock**

Fox Float Factory

Rider Weight (lbs)	(kgs)	Pressure (psi)	Sag (% mm on shock)	Rebound (from closed)
100	45	110	29-32%, 13-14.5mm	9
120	54	135	29-32%, 13-14.5mm	9
140	64	160	29-32%, 13-14.5mm	8
160	73	185	29-32%, 13-14.5mm	8
180	82	210	29-32%, 13-14.5mm	7
200	91	235	29-32%, 13-14.5mm	7
220	100	260	29-32%, 13-14.5mm	6
240	109	285	29-32%, 13-14.5mm	6
260	118	310	29-32%, 13-14.5mm	5

Fork

Rockshox Pike Ultimate 130

Rider Weight (lbs)	(kgs)	Pressure (psi)	Rebound (from closed)	Compression: LSC,HSC (from closed)
100	45	50	12	9,4
120	54	60	11	9,4
140	64	70	10	9,4
160	73	80	10	9,4
180	82	90	9	9,4
200	91	100	7	9,4
220	100	110	6	9,4
240	109	120	5	9,4